





T8 Polylux XLRTM - G13 Cap FT8/36W/840/GE/CVG/BULK25

19114



Product information

Polylux XLr™ lamps should be the natural choice for all fluorescent lighting applications. The excellent colour reproduction flatters skin tones making people appear more natural, and makes merchandise appear more vibrant and colourful.

GE Lighting FTS/SS/NUTLY/SF/C

43 kWh/1000h

Application areas



Retail



Office



Education



Industrial







Product data

Cap/Base	G13
Bulb Shape	Tubular
Bulb Diameter [mm]	26
Net weight per piece [g]	240
Gross weight per piece [g]	288
Regulatory comment	EUP related
Brand	General Electric (GE)

Performance data

Colour Rendering Index (CRI) [Ra]	85
Nominal correlated colour temperature (CCT) [K]	4000
Nominal lumens [lm]	3250
Rated efficacy [LpW]	90
Energy efficiency class (EEC)	A
Rated Life [h]	15000
Weighted energy consumption [kWh/1000h]	42.29

Electrical data

Rated power [W] 36.	0
---------------------	---





Logistic data

DUN Code	10043168191149	
EAN Code	0043168191142	
Pack Quantity	25	
Inner pack type	BULK PACKED	
Outer pack type	OUTER BOX	
Layer quantity	100 EUR, 150 UK	
Layer quantity EUR	100	
Layer quantity UK	150	
Pallet quantity EUR (PC)	600	
Pallet quantity UK (PC)	900	
Outer case size	1265 × 176 × 160 (mm)	
Product status	Available	

Downloads & Links

Go to the catalog site (HTTP)

Linear Fluorescent Lamps Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)