



LTO Ultrium

Meeting the Needs of a Broad Market

WHY CHOOSE QUANTUM LTO ULTRIUM MEDIA:

- Quantum's LTO Ultrium media is manufactured to the highest industry standards for quality and reliability ensuring high-performance and durability, whether utilized for primary backup or long-term archive.
- A pioneer of the LTO Consortium, Quantum is committed to the continued development of the LTO platform. Quantum's comprehensive media quality monitoring and extensive interoperability testing ensures cross-platform compatibility, optimal performance, and reliability whether you're using a Quantum tape drive, library, or other LTO compatible hardware.
- Quantum's LTO Ultrium media is compliant with all Media Integrity Analysis utilities, including Quantum's iLayer Advanced Reporting and Extended Data Life Management, to provide ongoing trend data to evaluate and protect the integrity of the media pool, helping administrators improve overall backup reliability and reduce costs. When your critical data is involved, it's important have a complete health record of your media.
- LTO Ultrium WORM (Write Once Read Many) media cartridges are available to meet today's stringent regulatory and compliance requirements. Combined with native AES 256-bit encryption on LTO-4 and LTO-5 drives, WORM cartridges physically prevent data from being overwritten or tampered with, providing a reliable, accurate and scalable data integrity solution.
- Quantum's LTO media offering supports your comprehensive, "edge to core" backup, recovery and archive strategy. When you use Quantum media and hardware, you get the added assurance of over 30 years of storage experience and service behind the entire solution.

QUANTUM OFFERS COMPLIMENTARY VALUE-ADDED SERVICES TO SAVE YOU TIME AND MONEY MANAGING YOUR MEDIA:

Have you ever spent hours unpacking, labeling and loading media into your library?
Why waste IT resources unpacking boxes and labeling cartridges?
Your time and your data are valuable. We understand that.

- Allow Quantum to pre-label your data cartridges with your requested bar code label sequences and color scheme. They'll arrive ready to load into the library.

No need for individual cartridge cases? No problem! We offer "library packaging" to save you time!

- This eco-friendly bulk packaging option protects cartridges during shipment and storage without the individual cartridge cases. This allows quicker access to the cartridges to expedite loading into automation slots/trays—and it results in less waste. Combine bar code labeling with library packaging and save even more time!

MEDIA

INDUSTRY LEADING QUALITY AND RELIABILITY

COMPATIBLE WITH QUANTUM AND OTHER BRAND LTO DRIVES AND LIBRARIES

COMPLIMENTARY VALUE ADDED SERVICES

ONE SOURCE FOR ALL YOUR DATA STORAGE AND SERVICE NEEDS

FEATURES AND BENEFITS

- **High Storage Capacity** – Up to 1500GB native and up to 3000GB compressed¹
- **Fast Transfer Rate** – Up to 280MB/sec¹ for quicker backup and improved cost efficiency
- **Up to 30 year archival life**
- **WORM (Write Once Read Many)** – Addresses today's tough regulatory and compliance needs
- **High-Performance** – a high-durability non-contact IC memory chip up to 8KB is built-in; this contributes to significant improvement in tape library access and health reporting
- **Bar code labeling and library packaging** available to quickly load automation slots/trays
- **Over 30 years of experience** – Demonstrated top performance and innovation in hardware and media products



	Ultrium 5 Ultrium 5 WORM	Ultrium 4 Ultrium 4 WORM	Ultrium 3 Ultrium 3 WORM	Ultrium 2	Ultrium 1	Ultrium Universal Cleaning
BASIC SPECIFICATIONS						
Drive Compatibility	LTO-5 LTO-5 WORM	LTO-4 LTO-4 WORM	LTO-3 LTO-3 WORM	LTO-2	LTO-1	All
Cartridge Color	Brick Red Brick Red/Gray	Green Green/Gray	Blue Blue/Gray	Purple	Black	Black
Capacity (Native/Compressed)	1500/3000GB ¹	800/1600GB ¹	400/800GB ¹	200/400GB ¹	100/200GB ¹	N/A
Number of Tracks	1280	896	704	512	384	N/A
Durability	Average 1,000,000+ head passes in office/computer environment	Average 1,000,000+ head passes in office/computer environment	Average 1,000,000+ head passes in office/computer environment	Average 1,000,000+ head passes in office/computer environment	Average 1,000,000+ head passes in office/computer environment	N/A
Uses	Up to 260 full tape uses WORM – Write once, read many, append only tape. Up to 260 full tape uses (Writes, appends or reads)	Up to 260 full tape uses WORM – Write once, read many, append only tape. Up to 260 full tape uses (Writes, appends or reads)	Up to 260 full tape uses WORM – Write once, read many, append only tape. Up to 260 full tape uses (Writes, appends or reads)	Up to 260 full tape uses	Up to 260 full tape uses	Maximum 50 cleanings – drive dependent
PHYSICAL CHARACTERISTICS						
Tape Width	12.65mm (0.50")	12.65mm (0.50")	12.65mm (0.50")	12.65mm (0.50")	12.65mm (0.50")	12.65mm (0.50")
Tape Thickness	6.4µm	6.6µm	8.0µm	8.9µm	8.9µm	8.0µm
Tape Length	846m (2776')	820m (2,690')	680m (2,231')	609m (1,998')	609m (1,998')	319m (1,046.59')
Cartridge Dimensions	21.5×105.4×102.0mm (0.85"×4.15"×4.02") [W × H × L]	21.5×105.4×102.0mm (0.85"×4.15"×4.02") [W × H × L]	21.5×105.4×102.0mm (0.85"×4.15"×4.02") [W × H × L]	21.5×105.4×102.0mm (0.85"×4.15"×4.02") [W × H × L]	21.5×105.4×102.0mm (0.85"×4.15"×4.02") [W × H × L]	21.5×105.4×102.0mm (0.85"×4.15"×4.02") [W × H × L]
OPERATING ENVIRONMENT						
Temperature	10 – 45°C (50 – 113°F)	10 – 45°C (50 – 113°F)	10 – 45°C (50 – 113°F)	10 – 45°C (50 – 113°F)	10 – 45°C (50 – 113°F)	10 – 45°C (50 – 113°F)
Humidity	10 – 80%RH	10 – 80%RH	10 – 80%RH	10 – 80%RH	10 – 80%RH	10 – 80%RH
STORAGE ENVIRONMENT – NON-ARCHIVE						
Temperature	16 – 32°C (61 – 90°F)	16 – 32°C (61 – 90°F)	16 – 32°C (61 – 90°F)	16 – 32°C (61 – 90°F)	16 – 32°C (61 – 90°F)	16 – 32°C (61 – 90°F)
Humidity	20 – 80%RH	20 – 80%RH	20 – 80%RH	20 – 80%RH	20 – 80%RH	20 – 80%RH
STORAGE ENVIRONMENT – ARCHIVE						
Temperature	16 – 25 °C (61 – 77°F)	16 – 25 °C (61 – 77°F)	16 – 25 °C (61 – 77°F)	16 – 25 °C (61 – 77°F)	16 – 25 °C (61 – 77°F)	N/A
Humidity	20 – 50%RH	20 – 50%RH	20 – 50%RH	20 – 50%RH	20 – 50%RH	N/A

¹ Based on 2:1 compression

Model Numbers and Descriptions

	Standard	WORM	Bar Code Labeled	Bar Code Labeled – WORM	Library Pack	Bar Code Labeled Library Pack
Ultrium 5	MR-L5MQN-01	MR-L5MQN-02	MR-L5MQN-BC	MR-L5WQN-BC	MR-L5MQN-20	MR-L5LQN-BC
Ultrium 4	MR-L4MQN-01	MR-L4MQN-02	MR-L4MQN-BC	MR-L4WQN-BC	MR-L4MQN-20	MR-L4LQN-BC
Ultrium 3	MR-L3MQN-01	MR-L3MQN-02	MR-L3MQN-BC	MR-L3WQN-BC	MR-L3MQN-20	MR-L3LQN-BC
Ultrium 2	MR-L2MQN-01		MR-L2MQN-BC		MR-L2MQN-20	MR-L2LQN-BC
Ultrium 1	MR-L1MQN-01		MR-L1MQN-BC			

For contact and product information, visit quantum.com or call 800-677-6268

Quantum®

Preserving the World's Most Important Data. Yours.™

©2011 Quantum Corporation. All rights reserved. Quantum, the Quantum logo, DXi, Scalar and StorNext are registered trademarks of Quantum Corporation and its affiliates in the United States and/or other countries. All other trademarks are the property of their respective owners.

About Quantum

Quantum Corp. (NYSE:QTM) is the leading global specialist in backup, recovery, and archive. From small businesses to multinational enterprises, more than 50,000 customers trust Quantum to solve their data protection, retention and management challenges. Quantum's best-of-breed, open systems solutions provide significant storage efficiencies and cost savings while minimizing risk and protecting prior investments. They include three market-leading, highly scalable platforms: DXi®-Series disk-based deduplication and replication systems for fast backup and restore, Scalar® tape automation products for disaster recovery and long-term data retention, and StorNext® data management software for high-performance file sharing and archiving. Quantum Corp., 1650 Technology Drive, Suite 800, San Jose, CA 95110, (408) 944-4000, www.quantum.com.