



COBA Guard Universal

Ideal for protecting floor surfaces from paint and debris whilst decorating. Sticks to both carpet and hard floors. Protects newly laid flooring when further building work is required. Universal - can be applied to most surfaces including carpet, laminate, tile and glass.

Technical Specifications:

- Manufactured from Polyethylene (PE)
- Flame retardant to BS 4790: 1987
- 80 microns thick

Dimensions (m.)	Weight Kg	Packaging Dimensions (cm.)	Packaging Type	Packaging Volume (m.)	Packaging Quantity	Colour	Part Code
0.6m x 10m		62 x 12 x 12				Transparent	CGU00001

Flame Retardancy: Conforms to BS 4790: 1987

Test Results

Sample	Time to extinction of flame (seconds)	Time to extinction of smouldering (seconds)	Radius of char (mm)
A	No Flaming	No Smouldering	10mm
B	No Flaming	No Smouldering	10mm
C	No Flaming	No Smouldering	10mm

Characteristics

Backing	PE(LDPE and LLDPE) film	
Adhesive	Acrylic solvent	
Colour	Transparent clear	
Adhesion strength	g/50mm	1000-1200
Tensile Strength	N/mm	≥45
Elongation	%	≥300
Temperature resistance	°C	60°C 160 hours.
Application temperature	°C	Cold temperature can affect the peel adhesion strength. Please apply the film at room temperature from 10 to 30°C

Continued on next page

United Kingdom

COBA Europe Ltd
Marlborough Drive
Fleckney, Leicestershire
LE8 8UR

+44 (0)116 240 1088
sales@cobaeeurope.com
www.cobaeeurope.com

Germany

COBA Europe GmbH
Pullenweg 1 - 3
41352 Korschenbroich

+49 (2161) 2945-0
verkauf@cobaeeurope.de
www.cobaeeurope.de

Slovakia

COBA Europe s.r.o.
Terchová - Vyšné Kamence 11
SK-013 06

+421 41 507 11 12
sales@cobaeeurope.sk
www.cobaeeurope.sk

The information contained within this datasheet is for guidance only. The data and suggested application are not exhaustive. All dimensions quoted are nominal figures. Please note that some products may be subject to a degree of shrinkage when installed into some applications.

Storage and Application

The product should be protected against direct sunlight and extremes in temperature and humidity and stored upright in its original packaging.

- The film should be applied within a 12 month period from the delivery date.
- The film should be removed within 6 months from the date of lamination :
 - within 3 months for carpet
 - within 6 months for all other surfaces if the product has been exposed outdoor
- Surface preparation is important. The substrate should be clean and free from residue, such as dust and oil, when the tape is applied in order to achieve optimum adhesion.
- Do not press too hard when applying. This may cause the end of the tape to peel.
- If applying to surfaces treated with machining oil, degrease the surface carefully. Any remains will be a cause for surface contamination or adhesive residue.

End of document**United Kingdom**

COBA Europe Ltd
Marlborough Drive
Fleckney, Leicestershire
LE8 8UR

☎ +44 (0)116 240 1088
✉ sales@cobaeeurope.com
🌐 www.cobaeeurope.com

Germany

COBA Europe GmbH
Pullenweg 1 - 3
41352 Korschenbroich

☎ +49 (2161) 2945-0
✉ verkauf@cobaeeurope.de
🌐 www.cobaeeurope.de

Slovakia

COBA Europe s.r.o.
Terchová - Vyšné Kamenec 11
SK-013 06

☎ +421 41 507 11 12
✉ sales@cobaeeurope.sk
🌐 www.cobaeeurope.sk

The information contained within this datasheet is for guidance only. The data and suggested application are not exhaustive. All dimensions quoted are nominal figures. Please note that some products may be subject to a degree of shrinkage when installed into some applications.