

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Artline **Xstamper**

Revision Date: 13th Jan. 2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name : Artline Permanent Marker Colour: (Black)

EK-30, EK-50, EK-70, EK-90, EK-100, EK-110, EK-120,

EK-130, EK-700 Artline marking INK

ESK-20, ESK-20-30, ESK-20-60, ESK-3, ESK-20-500

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Permanent marker ink 1.3. Details of the supplier of the safety data sheet

Supplier Company Name : Shachihata (Europe) Limited

> Address : Unit 8, Ashville Way, Sutton Weaver, Runcorn, Cheshire, WA7 3EZ, England

Telephone : 0870 600 5 006 : 0871 200 5 006 Fax

Contact (e-mail) : www.artline-xstamper.com

Manufacturer Company Name : Shachihata Inc.

> Address : 4-69, Amazuka-cho, Nishi-ku, Nagoya City, 451-0021, Japan

Telephone : +81-52-521-3600 : +81-52-521-3899 Fax

Contact (e-mail) : chem-analysis@ngy.shachihata.co.jp

1.4. Emergency telephone number

Telephone: 0870 600 5 006

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225 : Highly flammable liquid and vapour Serious eye damage, Category 1 H318 : Causes serious eye damage

2.2. Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Danger

: Highly flammable liquid and vapour Hazard statement

Causes serious eye damage

Precautionary statement

Wear eye protection.

[Prevention]

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharge.

[Response]

In case of fire: Use dry chemical powder, form or carbon dioxide to extinguish.

IF IN EYES: Rinse cautiously with water for several minutes.



Artline 70 @

Artline90 ©





(H225)

(H318)

(P101)

(P102)

(P210)

(P243)

(P280)

(P305+P351+P338)

Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice and attention.

Immediately call a POISON CENTER or physician.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. (P303+P361+P353)

If skin irritation occurs: Get medical advice and attention.

(P332+P313)

(P337+P313)

(P310)

[Storage]

Store in a well-ventilated place. Keep container tightly closed.

(P403+P233)

[Disposal]

Dispose of contents and container in accordance with local regulations.

(P501)

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Ingredients:

Chemical Name / Generic name	Composition weight %	CAS-No. EC-No. Index	Classification (REGULATION (EC) No 1272/2008)	
			Hazard Class	Hazard statement
Ethanol	50 ~ 60	64-17-5 200-578-6	Flam.Liq. 2	H225
Propan-1-ol	1 ~ 10	71-23-8 200-746-9	Flam.Liq. 2 Eye Dam. 1 STOT.SE. 3	H225 H318 H336
Ethyl lactate	10 ~ 20	97-64-3 202-598-0	Flam.Liq. 3 Eye Dam. 1 STOT.SE. 3	H226 H318 H335
Benzyl alcohol	1 ~ 5	100-51-6 202-859-9	Acute Tox.(oral) 4 Acute Tox.(inhal.) 4	H302 H332

SECTION 4: First aid measures

4.1. Description of first aid measures

IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Consult a doctor if symptoms persist.

IF ON SKIN : Remove/Take off immediately all contaminated clothing. Wash with soap and water.

If skin irritation/rash occurs or feel unwell, consult a doctor for medical advice.

IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

IF SWALLOWED : After rinse mouth immediately, give about 250 ml of water or milk and thin in the stomach,

and do not vomit forcibly. Moreover, do not give anything from the mouth to the patient

when not conscious. Receive the doctor's treatment (stomach pump) promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical powder, foam or carbon dioxide

Unsuitable extinguishing media : Water jet

5.2. Special hazards arising from the substance or mixture

For initial stage extinction, carbon dioxide or dry chemical powder.

When a fire extends, fire is extinguished by a large amount of water spray.

Do not discharge extinguishing waters into the aquatic environment.

5.3. Advice for firefighters

In the extinction work, an appropriate protective equipment (gloves, glasses, and mask) has to be worn.

Because during a fire, hazardous gases may be generated, fire-fighters have to wear self-contained breathing apparatus and other protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe area. Shut off all sources of ignition.

No Flares, smoking or flame in area. Put on protective equipment. Ensure adequate ventilation.

6.2. Environmental precautions

Do not throw the leakage thing directly into environment

6.3. Methods and material for containment and cleaning up

In case of a small spill, remove by absorbing with absorbents (sawdust, soil, sand, waste cloth, etc.),

and then wipe off the waste well with waste cloth, and rag.

In case of large spills, prevent leakage by enclosing with nonflammables (earth and sand, etc.)

and collect into empty container by scoop, suction equipment or the like.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling : Use with adequate ventilation.

Avoid contact with skin, eyes and clothing. Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep containers tightly closed and store in a cool and dry place.

areas and containers Keep away from heat and flame, ignition source and sunlight.

Keep out of the reach of children.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DIRECTIVE 2000/39/EC Not listed
DIRECTIVE 2006/15/EC Not listed
DIRECTIVE 2009/161/EU Not listed

EH40/2005 Workplace exposure limits

Ethanol TWA 1000ppm Propan-1-ol TWA 200ppm

ACGIH (2015)

Ethanol STEL 1000ppm Propan-1-ol TWA 100ppm

8.2. Exposure controls

Hq

Personal protective equipment

Respiratory Protection : Use with local exhaust ventilation, when in long use.

Avoid breathing vapours. Wear mask to prevent organic gas, if necessary.

Hand Protection : Avoid contact with hands. Wear safety gloves, if necessary. Eye Protection : Avoid contact with eyes. Wear safety glasses, if necessary.

: Not applicable

Skin Protection : Avoid skin contact. Wear personal protection apron, boots, if necessary.

Environmental exposure controls

General advice : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : black liquid

Odour : minor solvent odour

•

Boiling point : No data available

((EC) No 1907/2006) [Shachihata Inc.] [ESK-20_black_f] 4/6

Flash point : $16.5 \,^{\circ}\text{C}$ (closed cup) Relative Density (at 25 $^{\circ}\text{C}$) : $0.85 \,^{\circ} \, 0.95$ (g/cm³)

Solubility in Water : Insoluble

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Thermally stable at typical use temperatures.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to Avoid

High temperature, Direct sunlight, Fire

10.5. Incompatible Materials

No data available

10.6. Hazardous decomposition products

CO, CO₂

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : LD/LC50 values that are relevant for classification

[Ethanol]

Oral-rat LD50 >5,000 mg/kg Inhalation-rat LC50 >20 mg/L/4h

[Propan-1-ol]

Oral-rat LD50 >2,000mg/kg
Dermal-rabbit LD50 >2,000mg/kg
Inhalation-rat LC50 >20 mg/L/4h

[Ethyl lactate]

Oral-rat LD50 >2,000mg/kg
Dermal-rabbit LD50 >5,000mg/kg

[Benzyl alcohol]

Oral-rat LD50 >300 - <=2,000 mg/kgInhalation-rat LC50 >10 - <=20 mg/L/4h

Serious eye damage : Category 1 Causes serious eye damage

Carcinogenicity : This product does not contain any component that is considered

a human carcinogen by IARC, ACGIH, EPA, EU or NTP .

SECTION 12: Ecological information

12.1. Toxicity: No data available12.2. Persistence and degradability: No data available12.3. Bioaccumulative potential: No data available12.4. Mobility in soil: No data available12.5. Results of PBT and vPvB assessment: No data available12.6. Other adverse effects: No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal must be made according to official regulations.

Comply with all Federal, State, and Local regulations regarding disposal.

Do not allow product to reach ground, any water course or sewage system.

SECTION 14: Transport information

14.1. UN number DOT, ADR, IMDG, IATA: UN1210

14.2. UN proper shipping name DOT, ADR, IMDG, IATA: PRINTING INK, flammable

14.3. Transport hazard class(es) DOT, ADR, IMDG, IATA:

· Class 3 (Flammable liquids)

· Label 3

14.4. Packing group DOT, ADR, IMDG, IATA : ${
m I\hspace{-.1em}I}$

14.5. Environmental hazards Marine pollutant : No

14.6. Special precautions for user EMS Number : F-E,S-D

14.7. Transport in bulk according to Annex II of : Not applicable.

MARPOL 73/78 and the IBC Code

☆☆

Artline Permanent Marker (EK-30,EK-70,EK-90,EK-700) is not a hazardous material by the special provision. However, Artline Permanent Marker (EK-50,EK-100,EK-110,EK-120,EK-130) is a hazardous material (UN3175) for more than 10ml.

Artline Permanent Marker (EK-30,EK-70,EK-90,EK-700) (The amount of ink: less than 10ml)

UN number : UN3175

UN proper shipping name : Solids containing Flammable Liquid. n.o.s.

IATA Special Provision A46
IMDG Code Special Provision 216

According to IATA Special Provision A46, and IMDG Code Special Provision 216, small inner packagings consisting of sealed packets and articles containing less than 10 mL of a Class 3 liquid in

Packing Group II or III absorbed onto a solid material are not subject to as a hazardous

material/dangerous goods provided there is no free liquid in the packet or article.

Artline Permanent Marker (EK-50,EK-100,EK-110,EK-120,EK-130) (The amount of ink: over 10ml)

UN number : UN3175

UN proper shipping name : Solids containing Flammable Liquid. n.o.s.

UN Classification : 4.1 Packing group : II

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

< EU Information >

Regulation (EC) No 1272/2008 (CLP)

Substance name : [Ethanol]

Hazard Class & Category : Flammable liquids, Category 2

Symbols : GHS02 Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour

Substance name : [Propan-1-ol]

Hazard Class & Category : Flammable liquids, Category 2

Serious eye damage, Category 1

Specific target organ toxicity - single exposure, Category 3

Symbols : GHS02,GHS07,GHS05

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour

H318 Causes serious eye damage

H336 May cause drowsiness or dizziness

Substance name : [Ethyl lactate]

Hazard Class & Category : Flammable liquids, Category 3

Serious eye damage, Category 1

Specific target organ toxicity - single exposure, Category 3

Symbols : GHS02,GHS07,GHS05

Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour

H318 Causes serious eye damageH335 May cause respiratory irritation



[(EC) No 1907/2006][Shachihata Inc.] [ESK-20_black_f] 6/6

Substance name : [Benzyl alcohol]

Hazard Class & Category : Acute toxicity - Oral, Category 4

Acute toxicity - Inhalation, Category 4

Symbols : GHS07 Signal word : Warning

Hazard statements : H302 Harmful if swallowed

H332 Harmful if inhaled

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information



EU RoHS Directive(2011/65/EC) ELV Directive(2000/53/EC) This data sheet may not be enough when evaluating danger or hazard. The above information, which is created from currently available documents, information and data, may be revised when new findings announced. This document has been written on the assumption that when dealing with a large amount of ink on the business case and emergency. When handling as a normal product, please refer to the notes that is described in the produce or packaging. The information contained herein is not intended to provide any kind of warranty other than information, there is no guarantee for the accuracy of the content.