Customer Benefits
<ul> <li>□ Excellent mobility due to very compact design and low weight</li> <li>□ Reliable 3 pistons axle pump</li> <li>□ Automatic pressure relief system for protecting the high pressure components</li> <li>□ Extendable push handle provides more convenience to customer during transportation</li> </ul>
Product Brief
The new HD 4/8 Classic is designed according to customer requirements in regards to mobility, flexibilit
Technical data
□ Power supply 220-240 v
□ Power supply 220-240 v □ Water flow rate 400 l/h
• • •
□ Water flow rate 400 l/h
□ Water flow rate 400 l/h □ Working pressure 80 bar / 8 Mpa
□ Water flow rate 400 l/h □ Working pressure 80 bar / 8 Mpa □ Max. pressure 120 bar □ Connected load 1.4 kW □ Max. temperature 40 degrees
□ Water flow rate 400 l/h □ Working pressure 80 bar / 8 Mpa □ Max. pressure 120 bar □ Connected load 1.4 kW

	The activity of	singa out the state	A ala alas faccos d		als for out	out-
y and reliability.	. i ne robust mach	imes are the righ	t choice for profe	essionals who see	ek for sufficient p	епо

rmance for occasional, easy o	cleanings jobs which might	be fulfilled in many cases	by consumer product

s so far.