

SAFETY DATA SHEET
PERMANENT SPRAYMOUNT 400ML

Page: 1

Compilation date: 29.06.2020

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PERMANENT SPRAYMOUNT 400ML

Product code: KF11026

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: INTERACTION

Jean-Baptiste de Ghellincklaan 23, box 101

9051 Gent

BELGIUM

+32 9 380 8248

Tel: +32 9 380 8249

Email: info@interaction-connect.com

1.4. Emergency telephone number

Emergency tel: Germany: Intoxications Information Center; +49 761 19240

Switzerland: Swiss Toxicological Information Centre; +41 44 251 51 51

Austria: Intoxication information center; +43 1 406 43 43

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: STOT SE 3: H336; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Flam. Aerosol 1: H222;
Skin Irrit. 2: H315; -: H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



[cont...]

SAFETY DATA SHEET
PERMANENT SPRAYMOUNT 400ML

Page: 2

Signal words: Danger

Precautionary statements: P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BUTANE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	45-50%

PROPANE

200-827-9	74-98-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	20-25%
-----------	---------	--	-------------------------------------	--------

ACETONE

200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	5-10%
-----------	---------	---	--	-------

HYDROCARBONS, C6, ISOALKANE, <5% N-HEXAN - REACH registered number(s): 01-2119484651-34

931-254-9	-	-	Flam. Liq. 2: H225; Asp. Tox. 1: H304; Aquatic Chronic 2: H411; Skin Irrit. 2: H315; STOT SE 3: H336	5-10%
-----------	---	---	--	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water.

Inhalation: Not applicable.

[cont...]

SAFETY DATA SHEET
PERMANENT SPRAYMOUNT 400ML

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

[cont...]

SAFETY DATA SHEET
PERMANENT SPRAYMOUNT 400ML

Page: 4

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

BUTANE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1450 mg/m ³	1810 mg/m ³	-	-

PROPANE

UK	1800 mg/m ³	7200 mg/m ³	-	-
----	------------------------	------------------------	---	---

ACETONE

UK	1210 mg/m ³	3620 mg/m ³	-	-
----	------------------------	------------------------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

- Engineering measures:** Ensure there is sufficient ventilation of the area.
- Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.
- Hand protection:** Protective gloves.
- Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.
- Skin protection:** Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- State:** Aerosol
- Colour:** Colourless
- Odour:** Characteristic odour
- Evaporation rate:** No data available.
- Oxidising:** Non-oxidising (by EC criteria)
- Solubility in water:** Insoluble

[cont...]

SAFETY DATA SHEET
PERMANENT SPRAYMOUNT 400ML

Page: 5

Viscosity: Not applicable.
Boiling point/range°C: <-20
Flash point°C: <-20
Autoflammability°C: Not applicable.
Relative density: 0.617 g/cm³

Melting point/range°C: Not applicable.
Part.coeff. n-octanol/water: No data available.
Vapour pressure: No data available.
pH: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

HYDROCARBONS, C6, ISOALKANE, <5% N-HEXAN

DERMAL	RAT	1H LC50	>3000	mg/kg
GASES	RAT	4H LC50	>20	mg/l

[cont...]

SAFETY DATA SHEET
PERMANENT SPRAYMOUNT 400ML

Page: 6

ORAL	RAT	LD50	>5000	mg/kg
------	-----	------	-------	-------

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

ACETONE

BLUEGILL (<i>Lepomis macrochirus</i>)	LC50	8300	mg/l
---	------	------	------

HYDROCARBONS, C6, ISOALKANE, <5% N-HEXAN

Daphnia magna	LC50/48h	3,87	mg/l
Oryzias latipes	LC50/48h	>1	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

[cont...]

SAFETY DATA SHEET
PERMANENT SPRAYMOUNT 400ML

Page: 7

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

[cont...]

SAFETY DATA SHEET
PERMANENT SPRAYMOUNT 400ML

Page: 8

H225: Highly flammable liquid and vapour.

H229: Pressurised container: May burst if heated.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.