

## Mail Lite® Uncoated Mailers

### PRODUCT SPECIFICATION SHEET

### CUSHIONED PROTECTIVE MAILERS

#### Physical Properties

|             |  |
|-------------|--|
| Composition | <p>Uncoated paper exterior with an interior of co-extruded plastic bubble film made from low-density polyethylene and plastic barrier. A hot melt adhesive is added to the exposed paper to create a sealing lip. A backing paper is used to protect the adhesive from losing tacking properties until required.</p> <p>Standard Mail Lite are printed with Sealed Air logo, size identification and readable barcoding. Paper is Chain of Custody (FSC) certified.</p> <p>Water-soluble inks are used for all printing designs.</p> |
|-------------|--|

| Mailer Code | Unit | External Sizes<br><i>Excluding Bottom Seal</i> | Internal Width |
|-------------|------|--|----------------|
| A/000       | mm   | 130 x 160                                      | 110            |
| B/00        | mm   | 140 x 210                                      | 120            |
| C/0         | mm   | 170 x 210                                      | 150            |
| D/1         | mm   | 200 x 260                                      | 180            |
| E/2         | mm   | 240 x 260                                      | 220            |
| F/3         | mm   | 240 x 330                                      | 220            |
| G/4         | mm   | 260 x 330                                      | 240            |
| H/5         | mm   | 290 x 360                                      | 270            |
| J/6         | mm   | 320 x 440                                      | 300            |
| K/7         | mm   | 370 x 470                                      | 350            |

| Physical Properties                   | Unit             | Value | Tolerances |
|---------------------------------------|------------------|-------|------------|
| External Width                        | mm               | -     | +/- 8      |
| Length excluding Lip                  | mm               | -     | +/- 8      |
| Lip                                   | mm               | -     | +/- 10     |
| Paper                                 | g/m <sup>2</sup> | 70    | + /- 2.1   |
| AirCap® bubble (60% recycled content) | g/m <sup>2</sup> | 40    | +/- 2      |
| Seam strength                         | N                | 7     | +/- 2      |
| Glue Strength                         | N                | 5     | +/- 2      |

NOTICE: While values shown are typical of this product, they should not be construed as specification limits. Sealed Air makes no warranties, express or implied, including without limitation, warranties of merchantability or fitness for a particular purpose, with respect to any product, information or recommendations referred to herein, and shall not be liable for any loss or damage, directly or indirectly, related to such product, information or recommendations or for consequential or incidental damages. User should test each application to determine suitability of the product for the intended use.