



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 13

Sellotape Sellotac Blue Adhesive Tack

SDS No. : 478055
V003.0

Revision: 23.11.2022

printing date: 27.09.2023

Replaces version from: 19.02.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Sellotape Sellotac Blue Adhesive Tack

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Adhesive pad

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Adhesives
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration $\geq 0,1\%$ and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration \geq the concentration limit that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. EC Number REACH-Reg No. | Concentration | Classification | Specific Conc. Limits, M-factors and ATEs | Add. Information |
|---|---------------|---------------------------|---|------------------|
| Quartz (SiO ₂), <1% respirable 14808-60-7 238-878-4 | 10- 20 % | | | |
| White mineral oil (petroleum) 8042-47-5 232-455-8 01-2119487078-27 | 10- 20 % | Asp. Tox. 1, H304 | | |
| Titanium dioxide 13463-67-7 236-675-5 01-2119489379-17 | 1- < 5 % | Carc. 2, Inhalation, H351 | | |

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact:

Rinse immediately with plenty of running water, seek medical advice if necessary.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media**Suitable extinguishing media:**

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO₂) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

No particular measures required.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, dry place.

Store protected from light.

Temperatures between + 5 °C and + 25 °C

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Adhesive pad

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|-----|-------------------|------------------------------|--|-----------------|
| Limestone 1317-65-3 [CALCIUM CARBONATE, INHALABLE DUST] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |
| Limestone 1317-65-3 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |
| Limestone 1317-65-3 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |
| Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Quartz (SiO ₂) 14808-60-7 [SILICA, RESPIRABLE CRYSTALLINE] | | 0,1 | Time Weighted Average (TWA): | | EH40 WEL |
| Quartz (SiO ₂) 14808-60-7 [RESPIRABLE CRYSTALLINE SILICA DUST] | | 0,1 | Time Weighted Average (TWA): | | EU OELIII |

Occupational Exposure Limits

Valid for
Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|------------------------------|--|-----------------|
| Limestone 1317-65-3 [CALCIUM CARBONATE] | | 4 | Time Weighted Average (TWA): | | IR_OEL |
| Limestone 1317-65-3 [CALCIUM CARBONATE] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| White mineral oil (petroleum) 8042-47-5 [MINERAL OILS THAT HAVE BEEN USED BEFORE IN INTERNAL COMBUSTION ENGINES TO LUBRICATE AND COOL THE MOVING PARTS WITHIN THE ENGINE] | | | Skin designation: | Can be absorbed through the skin. | IR_OEL |
| White mineral oil (petroleum) 8042-47-5 [MINERAL OILS THAT HAVE BEEN USED BEFORE IN INTERNAL COMBUSTION ENGINES TO LUBRICATE AND COOL THE MOVING PARTS WITHIN THE ENGINE] | | | | Included in the regulation but with no data values. See regulation for further details | IR_OEL |
| White mineral oil (petroleum) 8042-47-5 [MINERAL OIL PURE, HIGHLY & SEVERELY REFINED] | | 5 | Time Weighted Average (TWA): | | IR_OEL |

| | | | | | |
|---|--|-----|------------------------------|--------------|-----------|
| Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE] | | 4 | Time Weighted Average (TWA): | | IR_OEL |
| Quartz (SiO ₂) 14808-60-7 [RESPIRABLE CRYSTALLINE SILICA DUST] | | 0,1 | Time Weighted Average (TWA): | | EU OELIII |
| Quartz (SiO ₂) 14808-60-7 [Silica, crystalline, respirable dust (Cristobalite, Quartz, Tridymite, Tripoli)] | | 0,1 | Time Weighted Average (TWA): | Binding OELV | IR_OEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|--|---------------------------|-----------------|-------|-----|-------|--------|----------------------|
| | | | mg/l | ppm | mg/kg | others | |
| White mineral oil (petroleum) 8042-47-5 | Air | | | | | | no hazard identified |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|--|--------------------|-------------------|---------------------------------------|---------------|-------------------------|----------------------|
| White mineral oil (petroleum) 8042-47-5 | Workers | Inhalation | Long term exposure - systemic effects | | 160 mg/m ³ | no hazard identified |
| White mineral oil (petroleum) 8042-47-5 | Workers | dermal | Long term exposure - systemic effects | | 220 mg/kg | no hazard identified |
| White mineral oil (petroleum) 8042-47-5 | General population | dermal | Long term exposure - systemic effects | | 93 mg/kg | no hazard identified |
| White mineral oil (petroleum) 8042-47-5 | General population | Inhalation | Long term exposure - systemic effects | | 35 mg/m ³ | no hazard identified |
| White mineral oil (petroleum) 8042-47-5 | General population | oral | Long term exposure - systemic effects | | 40 mg/kg | no hazard identified |
| Titanium dioxide 13463-67-7 | Workers | inhalation | Long term exposure - local effects | | 0,17 mg/m ³ | |
| Titanium dioxide 13463-67-7 | General population | inhalation | Long term exposure - local effects | | 0,028 mg/m ³ | |

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:
Not needed.

Hand protection:
material thickness > 0.1 mm
Perforation time > 480 minutes

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:
Not needed.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|-------------------------------|
| Delivery form | liquid |
| Colour | white |
| Odor | odourless |
| Physical state | liquid |
| Melting point | Currently under determination |
| Initial boiling point | > 316 °C (> 600.8 °F) |
| Flammability | Currently under determination |
| Explosive limits | Currently under determination |
| Flash point | Not applicable |
| Auto-ignition temperature | Currently under determination |
| Decomposition temperature | Currently under determination |
| pH | Not applicable |
| Viscosity (kinematic) | Currently under determination |
| Solubility (qualitative) | Insoluble |
| (23 °C (73.4 °F); Solvent: Water) | |
| Partition coefficient: n-octanol/water | Currently under determination |
| Vapour pressure | Currently under determination |
| Density | 1,7 g/ml Supplier method |
| (20 °C (68 °F)) | |
| Relative vapour density: | 1,8 |
| (20 °C) | |
| Particle characteristics | Currently under determination |

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with acids: production of heat and carbon dioxide.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|---------------|---------------|---------|---|
| Quartz (SiO ₂), <1% respirable 14808-60-7 | LD50 | > 5.050 mg/kg | rat | not specified |
| White mineral oil (petroleum) 8042-47-5 | LD50 | > 5.000 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| Titanium dioxide 13463-67-7 | LD50 | > 5.000 mg/kg | rat | OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure) |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|---------------|----------------|---------------|--|
| Quartz (SiO ₂), <1% respirable 14808-60-7 | LD50 | > 2.000 mg/kg | not specified | not specified |
| White mineral oil (petroleum) 8042-47-5 | LD50 | > 2.000 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |
| Titanium dioxide 13463-67-7 | LD50 | > 10.000 mg/kg | rabbit | not specified |

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Test atmosphere | Exposure time | Species | Method |
|---|---------------|-------------|-----------------|------------------|---------|--|
| White mineral oil (petroleum) 8042-47-5 | LC50 | > 5 mg/l | dust/mist | 4 h | rat | OECD Guideline 403 (Acute Inhalation Toxicity) |
| Titanium dioxide 13463-67-7 | LC50 | > 6,82 mg/l | dust | 4 h | rat | not specified |

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|---|----------------|------------------|---------|--|
| White mineral oil (petroleum) 8042-47-5 | not irritating | | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| Titanium dioxide 13463-67-7 | not irritating | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|---|----------------|------------------|---------|---|
| White mineral oil (petroleum) 8042-47-5 | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Titanium dioxide 13463-67-7 | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|---|-----------------|---------------------------------------|------------|--|
| White mineral oil (petroleum) 8042-47-5 | not sensitising | Buehler test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| Titanium dioxide 13463-67-7 | not sensitising | Mouse local lymphnode assay (LLNA) | mouse | equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| Titanium dioxide 13463-67-7 | not sensitising | Buehler test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|---|----------|--|--|---------|--|
| White mineral oil (petroleum) 8042-47-5 | negative | bacterial reverse mutation assay (e.g Ames test) | with | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| White mineral oil (petroleum) 8042-47-5 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Titanium dioxide 13463-67-7 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Titanium dioxide 13463-67-7 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Titanium dioxide 13463-67-7 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Titanium dioxide 13463-67-7 | negative | in vitro mammalian cell micronucleus test | without | | equivalent or similar to OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test) |
| White mineral oil (petroleum) 8042-47-5 | negative | intraperitoneal | | mouse | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |
| Titanium dioxide 13463-67-7 | negative | oral: gavage | | rat | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Sex | Method |
|---------------------------------|------------------|-------------------------|---|---------|-------------|---------------|
| Titanium dioxide 13463-67-7 | not carcinogenic | oral: feed | 103 w daily | rat | male/female | not specified |

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|---|---|-----------------------------|-------------------------|---------|---|
| White mineral oil (petroleum) 8042-47-5 | NOAEL P >= 2.000 mg/kg NOAEL F1 >= 2.000 mg/kg | one- generation study | dermal | rat | OECD Guideline 415 (One- Generation Reproduction Toxicity Study) |
| Titanium dioxide 13463-67-7 | NOAEL P >= 1.000 mg/kg NOAEL F1 >= 1.000 mg/kg | one- generation study | oral: feed | rat | OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study) |

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|---|-------------------------|-------------------------|--|---------|--|
| White mineral oil (petroleum) 8042-47-5 | NOAEL >= 1.600 mg/kg | oral: feed | 90 d daily | rat | OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) |
| Titanium dioxide 13463-67-7 | NOAEL > 1.000 mg/kg | oral: gavage | 92 d daily | rat | OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) |

Aspiration hazard:

The mixture is classified based on Viscosity data.

| Hazardous substances CAS-No. | Viscosity (kinematic) Value | Temperature | Method | Remarks |
|---|--------------------------------|-------------|---------------|---------|
| White mineral oil (petroleum) 8042-47-5 | ca. 3,8 mm ² /s | 40 °C | not specified | |

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|--------------------------------|---------------|---------------------|---|
| Quartz (SiO ₂), <1% respirable 14808-60-7 | LC50 | > 1.000 mg/l | 96 h | not specified | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| White mineral oil (petroleum) 8042-47-5 | LL50 | > 100 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Titanium dioxide 13463-67-7 | LC50 | Toxicity > Water solubility | 48 h | Leuciscus idus | OECD Guideline 203 (Fish, Acute Toxicity Test) |

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|--------------------------------|---------------|---------------|--|
| Quartz (SiO ₂), <1% respirable 14808-60-7 | EC50 | > 1.000 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| White mineral oil (petroleum) 8042-47-5 | EL50 | > 100 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Titanium dioxide 13463-67-7 | EC50 | Toxicity > Water solubility | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|--------------------------------|---------------|---------------|--|
| White mineral oil (petroleum) 8042-47-5 | NOEL | 10 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Titanium dioxide 13463-67-7 | NOEC | Toxicity > Water solubility | 21 d | Daphnia magna | OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test) |

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|--------------------------------|---------------|---------------------------------|--|
| Quartz (SiO ₂), <1% respirable 14808-60-7 | EC50 | > 1.000 mg/l | 72 h | not specified | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| White mineral oil (petroleum) 8042-47-5 | NOELR | 100 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Titanium dioxide 13463-67-7 | EC50 | Toxicity > Water solubility | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Titanium dioxide 13463-67-7 | NOEC | Toxicity > Water solubility | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|--------------------------------|---------------|-------------------------|--|
| Quartz (SiO ₂), <1% respirable 14808-60-7 | EC0 | > 1.000 mg/l | 3 h | not specified | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |
| White mineral oil (petroleum) 8042-47-5 | IC50 | > 100 mg/l | 93 d | other: | other guideline: |
| Titanium dioxide 13463-67-7 | EC0 | Toxicity > Water solubility | 24 h | Pseudomonas fluorescens | DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test) |

12.2. Persistence and degradability

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|--|----------------------------|-----------|---------------|------------------|---|
| White mineral oil (petroleum) 8042-47-5 | not readily biodegradable. | aerobic | 31,3 % | 28 d | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|--|--------|-------------|---------------------------------------|
| White mineral oil (petroleum) 8042-47-5 | > 4 | | EU Method A.8 (Partition Coefficient) |

12.5. Results of PBT and vPvB assessment

| Hazardous substances CAS-No. | PBT / vPvB |
|--|---|
| Quartz (SiO ₂), <1% respirable 14808-60-7 | According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances. |
| White mineral oil (petroleum) 8042-47-5 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Titanium dioxide 13463-67-7 | According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances. |

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:
Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:
Use packages for recycling only when totally empty.

Waste code
080410

SECTION 14: Transport information

- 14.1. UN number or ID number**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Maritime transport in bulk according to IMO instruments**
not applicable

SECTION 15: Regulatory information

No information available:

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|---|----------------|
| Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): | Not applicable |
| Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): | Not applicable |
| Persistent organic pollutants (Regulation (EU) 2019/1021): | Not applicable |

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H304 May be fatal if swallowed and enters airways.

H351 Suspected of causing cancer.

| | |
|-------------|---|
| ED: | Substance identified as having endocrine disrupting properties |
| EU OEL: | Substance with a Union workplace exposure limit |
| EU EXPLD 1: | Substance listed in Annex I, Reg (EC) No. 2019/1148 |
| EU EXPLD 2: | Substance listed in Annex II, Reg (EC) No. 2019/1148 |
| SVHC: | Substance of very high concern (REACH Candidate List) |
| PBT: | Substance fulfilling persistent, bioaccumulative and toxic criteria |
| PBT/vPvB: | Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria |
| vPvB: | Substance fulfilling very persistent and very bioaccumulative criteria |

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.