

## 101 Rubber Adhesive

Component:	Hook Tape	Nylon/ Polyester
	Loop Tape	Nylon/ Polyester
	Surface Yarn	Nylon
	Ground Yarn	Polyester

### Technical Data

<b>Weight:</b>	Hook	0.036gm/square cm +/- 7%
	Loop	0.035gm/square cm +/- 7%

### Width Tolerance:

Thickness	Hook	2mm+/-0.1mm
	Loop	2mm+/-0.1mm

Density	Hook	≥37per square cm
	Loop	≥77per square cm

**Breaking Strength** ≥20KG/CM


### Peel Strength

CNS12649-L3227 160 g/cm



### Shear Strength

CNS12649-L3227 0.67 kg/cm



### Colour Fastness

Colours other than black or white would be at grade 2~3.

### Temperature resistance

According to the character of nylon, the melting point is 210C and the softening 160C.

We do not suggest use at this high temperature because the nylon will be deformed at this temperature and decrease the peeling/shearing strength.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because HALCO Europe cannot accept responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.